



Drive Chain Sprockets

Sprocket Number US-64S

For Union Chain Numbers US-64S, US-64SH

All dimensions are in inches unless otherwise specified.

2.500 Pitch				1.562 Roller Diameter 1.250 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
9	US-64SA9	1.50	15.0	US-64SC9	1.50	2.44	7.310	4.00	2.75	19.0
10	US-64SA10	1.50	18.0	US-64SC10	1.50	2.94	8.090	4.75	3.13	27.0
11	US-64SA11	1.50	22.0	US-64SC11	1.50	3.19	8.874	5.25	3.88	36.0
12	US-64SA12	1.50	26.0	US-64SC12	1.50	3.44	9.659	5.50	4.25	46.0
13	US-64SA13	1.50	30.0	US-64SC13	1.50	3.44	10.446	5.50	4.25	51.0
14	US-64SA14	1.50	35.0	US-64SC14	1.50	3.44	11.235	5.50	4.25	56.0
15	US-64SA15	1.50	40.0	US-64SC15	1.50	3.44	12.024	5.50	4.25	61.0
17	US-64SA17	1.50	52.0	US-64SC17	1.50	3.44	13.605	5.50	4.25	72.0
19	US-64SA19	1.50	64.0	US-64SC19	1.50	3.94	15.189	6.50	5.00	97.0
21	US-64SA21	1.50	78.0	US-64SC21	1.50	3.94	16.774	6.50	5.00	111.0
24	US-64SA24	1.50	102.0	US-64SC24	1.50	3.94	19.153	6.50	5.00	135.0
30 ¹	US-64SA30	1.50	144.0	US-64SC30	1.50	4.44	23.917	7.00	6.00	193.0
36 ¹	US-64SA36	1.50	188.0	US-64SC36	1.50	4.44	28.684	7.00	6.00	236.0
42 ¹	US-64SA42	1.50	241.0	US-64SC42	1.50	5.44	33.454	8.00	6.25	308.0
48 ¹	US-64SA48	1.50	301.0	US-64SC48	1.50	5.44	38.224	8.00	6.25	367.0
54 ¹	US-64SA54	1.50	354.0	US-64SC54	1.50	5.44	42.996	8.00	6.25	420.0
60 ¹	US-64SA60	1.50	418.0	US-64SC60	1.50	5.94	47.768	9.00	6.50	510.0

¹Furnished standard with lightening holes.

Sprocket Number US-882

For Union Chain Number US-882

All dimensions are in inches unless otherwise specified.

2.609 Pitch				.875 Roller Diameter .875 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
8	US-882A8	1.25	9.0	US-882C8	1.25	2.94	6.817	4.75	3.13	19.0
9	US-882A9	1.25	11.0	US-882C9	1.25	3.19	7.628	5.25	3.88	28.0
10	US-882A10	1.25	14.0	US-882C10	1.25	3.19	8.442	5.25	3.88	31.0
11	US-882A11	1.25	17.0	US-882C11	1.25	3.19	9.260	5.25	3.88	34.0
12	US-882A12	1.25	20.0	US-882C12	1.25	3.19	10.080	5.25	3.88	37.0
13	US-882A13	1.50	23.0	US-882C13	1.50	3.44	10.901	5.50	4.25	44.0
14	US-882A14	1.50	27.0	US-882C14	1.50	3.44	11.724	5.50	4.25	47.0
15	US-882A15	1.50	31.0	US-882C15	1.50	3.44	12.548	5.50	4.25	51.0
17	US-882A17	1.50	39.0	US-882C17	1.50	3.44	14.198	5.50	4.25	58.0
19	US-882A19	1.50	49.0	US-882C19	1.50	3.94	15.851	6.50	5.00	86.0
21	US-882A21	1.50	60.0	US-882C21	1.50	3.94	17.505	6.50	5.00	97.0
24	US-882A24	1.50	78.0	US-882C24	1.50	3.94	19.988	6.50	5.00	115.0
25	US-882A25	1.50	85.0	US-882C25	1.50	3.94	20.816	6.50	5.00	121.0
28	US-882A28	1.50	106.0	US-882C28	1.50	3.94	23.302	6.50	5.00	142.0
30 ¹	US-882A30	1.50	122.0	US-882C30	1.50	3.94	24.959	6.50	5.00	134.0
35 ¹	US-882A35	1.50	165.0	US-882C35	1.50	3.94	29.105	6.50	5.00	156.0
40 ¹	US-882A40	1.50	216.0	US-882C40	1.50	4.44	33.252	7.00	6.00	206.0
42 ¹	US-882A42	1.50	238.0	US-882C42	1.50	4.44	34.912	7.00	6.00	215.0
46 ¹	US-882A46	1.50	285.0	US-882C46	1.50	4.44	38.231	7.00	6.00	235.0
54 ¹	US-882A54	1.50	393.0	US-882C54	1.50	5.44	44.870	8.00	6.25	308.0
60 ¹	US-882A60	1.50	485.0	US-882C60	1.50	5.44	49.851	8.00	6.25	340.0

¹Furnished standard with lightening holes.

Sprocket Number 344SXX

For Union Chain Number 344SXX

3.000 Pitch				1.781 Roller Diameter 1.750 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
8	344SXXA8	1.50	24.0	344SXXC8	1.50	2.94	7.839	4.75	3.12	30.0
9	344SXXA9	1.50	30.0	344SXXC9	1.50	3.44	8.771	5.50	4.25	47.0
10	344SXXA10	1.50	37.0	344SXXC10	1.50	3.94	9.708	6.50	5.00	65.0
11	344SXXA11	1.50	44.0	344SXXC11	1.50	4.44	10.648	7.00	6.00	88.0
12	344SXXA12	1.50	52.0	344SXXC12	1.50	4.44	11.591	7.00	6.00	96.0
13	344SXXA13	1.50	61.0	344SXXC13	1.50	5.44	12.536	8.00	6.25	121.0
14	344SXXA14	1.50	71.0	344SXXC14	1.50	5.44	13.482	8.00	6.25	130.0
15	344SXXA15	1.50	81.0	344SXXC15	1.50	5.44	14.429	8.00	6.25	141.0
17	344SXXA17	1.50	104.0	344SXXC17	1.50	5.94	16.327	9.00	6.50	187.0
19	344SXXA19	1.50	130.0	344SXXC19	1.50	5.94	18.227	9.00	6.50	212.0
21	344SXXA21	1.50	158.0	344SXXC21	1.50	5.94	20.129	9.00	6.50	241.0
24	344SXXA24	1.50	206.0	344SXXC24	1.50	6.50	22.984	10.00	6.75	314.0
30	344SXXA30	1.50	321.0	344SXXC30	1.50	6.50	28.700	10.00	6.75	430.0
36 ¹	344SXXA36	1.50	407.0	344SXXC36	1.50	7.00	34.421	11.00	7.75	565.0
42 ¹	344SXXA42	1.50	522.0	344SXXC42	1.50	7.00	40.144	11.00	7.75	680.0
48 ¹	344SXXA48	1.50	654.0	344SXXC48	1.50	7.00	45.869	11.00	7.75	812.0

¹Furnished standard with lightening holes.



UNION CHAIN DIVISION - DRIVE CHAIN SPROCKETS

Sprocket Number US-3011

For Union Chain Number US-3011

All dimensions are in inches unless otherwise specified.

3.067 Pitch				1.625 Roller Diameter 1.250 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
8	US-3011A8	1.25	18.0	US-3011C8	1.25	2.94	8.014	4.75	3.12	20.0
9	US-3011A9	1.25	22.0	US-3011C9	1.25	3.19	8.967	5.25	3.88	37.0
10	US-3011A10	1.50	27.0	US-3011C10	1.50	3.44	9.925	5.50	4.25	48.0
11	US-3011A11	1.50	33.0	US-3011C11	1.50	3.44	10.886	5.50	4.25	53.0
12	US-3011A12	1.50	39.0	US-3011C12	1.50	3.44	11.850	5.50	4.25	60.0
13	US-3011A13	1.50	46.0	US-3011C13	1.50	3.44	12.816	5.50	4.25	66.0
14	US-3011A14	1.50	53.0	US-3011C14	1.50	3.44	13.783	5.50	4.25	73.0
15	US-3011A15	1.50	61.0	US-3011C15	1.50	3.94	14.751	6.50	5.00	93.0
17	US-3011A17	1.50	78.0	US-3011C17	1.50	3.94	16.691	6.50	5.00	110.0
19	US-3011A19	1.50	97.0	US-3011C19	1.50	3.94	18.634	6.50	5.00	129.0
21	US-3011A21	1.50	118.0	US-3011C21	1.50	3.94	20.578	6.50	5.00	150.0
24	US-3011A24	1.50	154.0	US-3011C24	1.50	4.44	23.497	7.00	6.00	204.0
30 ¹	US-3011A30	1.50	244.0	US-3011C30	1.50	4.44	29.341	7.00	6.00	252.0
36 ¹	US-3011A36	1.50	345.0	US-3011C36	1.50	5.44	35.190	8.00	6.25	341.0
42 ¹	US-3011A42	1.50	470.0	US-3011C42	1.50	5.44	41.041	8.00	6.25	404.0
48 ¹	US-3011A48	1.50	613.0	US-3011C48	1.50	5.44	46.894	8.00	6.25	462.0

¹Furnished standard with lightening holes.

Sprocket Number US-3075

For Union Chain Numbers US-3075, US-1031, US-1030, 30701, US-1032

3.075 Pitch				1.250 Roller Diameter 1.250 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
8	US-3075A8	1.25	18.0	US-3075C8	1.25	3.19	8.035	5.25	3.88	33.0
9	US-3075A9	1.25	22.0	US-3075C9	1.25	3.19	8.991	5.25	3.88	37.0
10	US-3075A10	1.50	27.0	US-3075C10	1.50	3.44	9.951	5.50	4.25	48.0
11	US-3075A11	1.50	33.0	US-3075C11	1.50	3.44	10.915	5.50	4.25	53.0
12	US-3075A12	1.50	39.0	US-3075C12	1.50	3.44	11.881	5.50	4.25	60.0
13	US-3075A13	1.50	46.0	US-3075C13	1.50	3.44	12.849	5.50	4.25	66.0
14	US-3075A14	1.50	53.0	US-3075C14	1.50	3.44	13.819	5.50	4.25	73.0
15	US-3075A15	1.50	61.0	US-3075C15	1.50	3.94	14.790	6.50	5.00	93.0
17	US-3075A17	1.50	78.0	US-3075C17	1.50	3.94	16.735	6.50	5.00	110.0
19	US-3075A19	1.50	97.0	US-3075C19	1.50	3.94	18.682	6.50	5.00	129.0
21	US-3075A21	1.50	119.0	US-3075C21	1.50	3.94	20.632	6.50	5.00	151.0
24 ¹	US-3075A24	1.50	155.0	US-3075C24	1.50	3.94	23.558	6.50	5.00	169.0
30 ¹	US-3075A30	1.50	241.0	US-3075C30	1.50	3.94	29.418	6.50	5.00	227.0
36 ¹	US-3075A36	1.50	347.0	US-3075C36	1.50	5.44	35.282	8.00	6.25	332.0
42 ¹	US-3075A42	1.50	472.0	US-3075C42	1.50	5.44	41.148	8.00	6.25	399.0
48 ¹	US-3075A48	1.50	616.0	US-3075C48	1.50	5.44	47.016	8.00	6.25	458.0

¹Furnished standard with lightening holes.

Sprocket Number US-3514

For Union Chain Number US-3514

All dimensions are in inches unless otherwise specified.

3.500 Pitch				1.750 Roller Diameter 1.250 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
8	US-3514A8	1.50	23.0	US-3514C8	1.50	3.62	9.146	5.75	5.00	49.0
9	US-3514A9	1.50	29.0	US-3514C9	1.50	4.44	10.233	7.00	6.00	78.0
10	US-3514A10	1.50	36.0	US-3514C10	1.50	4.44	11.326	7.00	6.00	85.0
11	US-3514A11	1.50	43.0	US-3514C11	1.50	5.44	12.423	8.00	6.25	111.0
12	US-3514A12	1.50	51.0	US-3514C12	1.50	5.44	13.523	8.00	6.25	119.0
13	US-3514A13	1.50	60.0	US-3514C13	1.50	5.44	14.625	8.00	6.25	127.0
14	US-3514A14	1.50	69.0	US-3514C14	1.50	5.44	15.729	8.00	6.25	137.0
15	US-3514A15	1.50	79.0	US-3514C15	1.50	5.44	16.834	8.00	6.25	147.0
17	US-3514A17	1.50	101.0	US-3514C17	1.50	5.94	19.048	9.00	6.50	193.0
19	US-3514A19	1.50	126.0	US-3514C19	1.50	5.94	21.264	9.00	6.50	218.0
21	US-3514A21	1.50	154.0	US-3514C21	1.50	6.50	23.483	10.00	6.75	273.0
24	US-3514A24	1.50	200.0	US-3514C24	1.50	6.50	26.815	10.00	6.75	320.0
30 ¹	US-3514A30	1.50	313.0	US-3514C30	1.50	7.00	33.484	11.00	7.75	435.0
36 ¹	US-3514A36	1.50	450.0	US-3514C36	1.50	7.00	40.158	11.00	7.75	521.0
42 ¹	US-3514A42	1.50	612.0	US-3514C42	1.50	7.00	46.835	11.00	7.75	614.0

¹Furnished standard with lightening holes.

Note: Sizes and hub styles other than listed above are available. Large segmental rim sprockets are available.

Sprocket Number US-1242

For Union Chain Number US-1242, US-1241

4.063 Pitch				1.750 Roller Diameter 1.750 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
9	US-1242A9	1.50	55.0	US-1242C9	1.50	4.44	11.879	7.00	6.00	99.0
10	US-1242A10	1.50	67.0	US-1242C10	1.50	5.44	13.148	8.00	6.25	129.0
11	US-1242A11	1.50	81.0	US-1242C11	1.50	5.44	14.421	8.00	6.25	142.0
12	US-1242A12	1.50	96.0	US-1242C12	1.50	5.44	15.698	8.00	6.25	157.0
13	US-1242A13	1.50	113.0	US-1242C13	1.50	5.44	16.978	8.00	6.25	174.0
14	US-1242A14	1.50	130.0	US-1242C14	1.50	5.94	18.259	9.00	6.50	213.0
15	US-1242A15	1.50	149.0	US-1242C15	1.50	5.94	19.542	9.00	6.50	232.0
17	US-1242A17	1.50	191.0	US-1242C17	1.50	5.94	22.112	9.00	6.50	273.0
19	US-1242A19	1.50	238.0	US-1242C19	1.50	6.50	24.685	10.00	6.75	346.0
21	US-1242A21	1.50	290.0	US-1242C21	1.50	6.50	27.261	10.00	6.75	398.0
24 ¹	US-1242A24	1.50	378.0	US-1242C24	1.50	6.50	31.128	10.00	6.75	453.0
30 ¹	US-1242A30	1.50	590.0	US-1242C30	1.50	7.00	38.870	11.00	7.75	649.0
36 ¹	US-1242A36	1.50	848.0	US-1242C36	1.50	7.00	46.618	11.00	7.75	830.0

¹Furnished standard with lightening holes.



UNION CHAIN DIVISION - DRIVE CHAIN SPROCKETS

U.S. TSUBAKI

Sprocket Number US-1245

For Union Chain Number US-1245

All dimensions are in inches unless otherwise specified.

4.073 Pitch				1.781 Roller Diameter 1.750 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
9	US-1245A9	1.50	55.0	US-1245C9	1.50	4.44	11.909	7.00	6.00	99.0
10	US-1245A10	1.50	68.0	US-1245C10	1.50	5.44	13.181	8.00	6.25	129.0
11	US-1245A11	1.50	82.0	US-1245C11	1.50	5.44	14.457	8.00	6.25	143.0
12	US-1245A12	1.50	97.0	US-1245C12	1.50	5.44	15.737	8.00	6.25	158.0
13	US-1245A13	1.50	113.0	US-1245C13	1.50	5.44	17.019	8.00	6.25	174.0
14	US-1245A14	1.50	131.0	US-1245C14	1.50	5.94	18.304	9.00	6.50	213.0
15	US-1245A15	1.50	150.0	US-1245C15	1.50	5.94	19.590	9.00	6.50	232.0
17	US-1245A17	1.50	192.0	US-1245C17	1.50	5.94	22.166	9.00	6.50	274.0
19	US-1245A19	1.50	239.0	US-1245C19	1.50	6.50	24.746	10.00	6.75	347.0
21	US-1245A21	1.50	292.0	US-1245C21	1.50	6.50	27.328	10.00	6.75	400.0
24 ¹	US-1245A24	1.50	380.0	US-1245C24	1.50	6.50	31.204	10.00	6.75	455.0
30 ¹	US-1245A30	1.50	593.0	US-1245C30	1.50	7.00	38.965	11.00	7.75	652.0
36 ¹	US-1245A36	1.50	852.0	US-1245C36	1.50	7.00	46.732	11.00	7.75	835.0

¹Furnished standard with lightening holes.

Sprocket Number US-4122

For Union Chain Number US-4122

4.090 Pitch				2.000 Roller Diameter 1.750 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
9	US-4122A9	1.50	56.0	US-4122C9	1.50	4.44	11.958	7.00	6.00	99.0
10	US-4122A10	1.50	68.0	US-4122C10	1.50	5.44	13.236	8.00	6.25	129.0
11	US-4122A11	1.50	82.0	US-4122C11	1.50	5.44	14.517	8.00	6.25	143.0
12	US-4122A12	1.50	97.0	US-4122C12	1.50	5.44	15.803	8.00	6.25	159.0
13	US-4122A13	1.50	114.0	US-4122C13	1.50	5.44	17.090	8.00	6.25	175.0
14	US-4122A14	1.50	132.0	US-4122C14	1.50	5.94	18.380	9.00	6.50	214.0
15	US-4122A15	1.50	151.0	US-4122C15	1.50	5.94	19.672	9.00	6.50	234.0
17	US-4122A17	1.50	193.0	US-4122C17	1.50	5.94	22.259	9.00	6.50	276.0
19	US-4122A19	1.50	241.0	US-4122C19	1.50	6.50	24.849	10.00	6.75	349.0
21	US-4122A21	1.50	294.0	US-4122C21	1.50	6.50	27.442	10.00	6.75	402.0
24 ¹	US-4122A24	1.50	383.0	US-4122C24	1.50	6.50	31.335	10.00	6.75	458.0
30 ¹	US-4122A30	1.50	598.0	US-4122C30	1.50	7.00	39.128	11.00	7.75	657.0
36 ¹	US-4122A36	1.50	860.0	US-4122C36	1.50	7.00	46.927	11.00	7.75	841.0

¹Furnished standard with lightening holes.

Sprocket Number US-4522

For Union Chain Number US-4522

All dimensions are in inches unless otherwise specified.

4.500 Pitch				2.250 Roller Diameter 1.750 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
10	US-4522A10	1.50	83.0	US-4522C10	1.50	5.44	14.562	8.00	6.25	144.0
11	US-4522A11	1.50	100.0	US-4522C11	1.50	5.44	15.973	8.00	6.25	161.0
12	US-4522A12	1.50	118.0	US-4522C12	1.50	5.44	17.387	8.00	6.25	179.0
13	US-4522A13	1.50	138.0	US-4522C13	1.50	5.44	18.804	8.00	6.25	199.0
14	US-4522A14	1.50	160.0	US-4522C14	1.50	5.94	20.223	9.00	6.50	242.0
15	US-4522A15	1.50	183.0	US-4522C15	1.50	5.94	21.644	9.00	6.50	265.0
17	US-4522A17	1.50	234.0	US-4522C17	1.50	5.94	24.490	9.00	6.50	317.0
19	US-4522A19	1.50	292.0	US-4522C19	1.50	6.50	27.340	10.00	6.75	400.0
21 ¹	US-4522A21	1.50	356.0	US-4522C21	1.50	6.50	30.193	10.00	6.75	439.0
24 ¹	US-4522A24	1.50	464.0	US-4522C24	1.50	6.50	34.476	10.00	6.75	519.0
30 ¹	US-4522A30	1.50	723.0	US-4522C30	1.50	7.00	43.050	11.00	7.75	714.0

¹Furnished standard with lightening holes.

Sprocket Number US-5035

For Union Chain Numbers US-5035, US-5031

5.000 Pitch				2.500 Roller Diameter 2.250 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
11	US-5035A11	1.50	158.0	US-5035C11	1.50	6.50	17.747	10.00	6.75	255.0
12	US-5035A12	1.50	187.0	US-5035C12	1.50	7.00	19.319	11.00	7.75	332.0
13	US-5035A13	1.50	219.0	US-5035C13	1.50	7.00	20.893	11.00	7.75	364.0
14	US-5035A14	1.50	253.0	US-5035C14	1.50	7.00	22.470	11.00	7.75	398.0
15	US-5035A15	1.50	290.0	US-5035C15	1.50	8.00	24.049	12.00	8.50	487.0
17	US-5035A17	1.50	372.0	US-5035C17	1.50	8.00	27.211	12.00	8.50	568.0
19	US-5035A19	1.50	463.0	US-5035C19	1.50	9.00	30.378	13.00	9.00	713.0
21	US-5035A21	1.50	565.0	US-5035C21	1.50	9.00	33.548	13.00	9.00	815.0
24 ¹	US-5035A24	1.50	736.0	US-5035C24	1.50	9.00	38.306	13.00	9.00	937.0
30 ¹	US-5035A30	1.50	1,148.0	US-5035C30	1.50	9.50	47.834	14.00	9.50	1,313.0

¹Furnished standard with lightening holes.



UNION CHAIN DIVISION - DRIVE CHAIN SPROCKETS

Sprocket Number US-5042

For Union Chain Number US-5042

All dimensions are in inches unless otherwise specified.

5.000 Pitch				3.000 Roller Diameter 2.500 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
11	US-5042A11	1.50	176.0	US-5042C11	1.50	6.50	17.747	10.00	6.75	267.0
12	US-5042A12	1.50	208.0	US-5042C12	1.50	6.50	19.319	10.00	6.75	299.0
13	US-5042A13	1.50	243.0	US-5042C13	1.50	7.00	20.893	11.00	7.75	381.0
14	US-5042A14	1.50	281.0	US-5042C14	1.50	7.00	22.470	11.00	7.75	419.0
15	US-5042A15	1.50	322.0	US-5042C15	1.50	7.00	24.049	11.00	7.75	460.0
17	US-5042A17	1.50	413.0	US-5042C17	1.50	8.00	27.211	12.00	8.50	601.0
19	US-5042A19	1.50	514.0	US-5042C19	1.50	8.00	30.378	12.00	8.50	703.0
21	US-5042A21	1.50	627.0	US-5042C21	1.50	9.00	33.548	13.00	9.00	868.0
24 ¹	US-5042A24	1.50	783.0	US-5042C24	1.50	9.00	38.306	13.00	9.00	1,023.0
30 ¹	US-5042A30	1.50	1,123.0	US-5042C30	1.50	9.00	47.834	13.00	9.00	1,364.0

¹Furnished standard with lightening holes.

Sprocket Number US-5542

For Union Chain Number US-5542

5.500 Pitch				3.000 Roller Diameter 2.500 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
11	US-5542A11	1.50	212.0	US-5542C11	1.50	6.50	19.522	10.00	6.75	304.0
12	US-5542A12	1.50	252.0	US-5542C12	1.50	7.00	21.250	11.00	7.75	390.0
13	US-5542A13	1.50	294.0	US-5542C13	1.50	7.00	22.982	11.00	7.75	432.0
14	US-5542A14	1.50	341.0	US-5542C14	1.50	7.00	24.717	11.00	7.75	478.0
15	US-5542A15	1.50	390.0	US-5542C15	1.50	8.00	26.454	12.00	8.50	579.0
17	US-5542A17	1.50	499.0	US-5542C17	1.50	8.00	29.932	12.00	8.50	688.0
19	US-5542A19	1.50	622.0	US-5542C19	1.50	9.00	33.415	13.00	9.00	863.0
21	US-5542A21	1.50	759.0	US-5542C21	1.50	9.00	36.902	13.00	9.00	1,000.0
24 ¹	US-5542A24	1.50	934.0	US-5542C24	1.50	9.00	42.137	13.00	9.00	1,174.0
30 ¹	US-5542A30	1.50	1,401.0	US-5542C30	1.50	9.50	52.617	14.00	9.50	1,701.0

¹Furnished standard with lightening holes.

C - SPROCKETS AND ACCESSORIES

Sprocket Number US-6042

For Union Chain Numbers US-6042, US-6066

All dimensions are in inches unless otherwise specified.

6.000 Pitch				3.000 Roller Diameter 2.500 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
11	US-6042A11	1.50	253.0	US-6042C11	1.50	6.50	21.297	10.00	6.75	344.0
12	US-6042A12	1.50	300.0	US-6042C12	1.50	7.00	23.182	11.00	7.75	437.0
13	US-6042A13	1.50	350.0	US-6042C13	1.50	7.00	25.071	11.00	7.75	488.0
14	US-6042A14	1.50	405.0	US-6042C14	1.50	7.00	26.964	11.00	7.75	543.0
15	US-6042A15	1.50	464.0	US-6042C15	1.50	8.00	28.858	12.00	8.50	653.0
17	US-6042A17	1.50	594.0	US-6042C17	1.50	8.00	32.653	12.00	8.50	783.0
19	US-6042A19	1.50	741.0	US-6042C19	1.50	9.00	36.453	13.00	9.00	981.0
21 ¹	US-6042A21	1.50	856.0	US-6042C21	1.50	9.00	40.257	13.00	9.00	1,097.0
24 ¹	US-6042A24	1.50	1,058.0	US-6042C24	1.50	9.00	45.968	13.00	9.00	1,298.0
30 ¹	US-6042A30	1.50	1,519.0	US-6042C30	1.50	9.50	57.401	14.00	9.50	1,820.0

¹Furnished standard with lightening holes.

Sprocket Number US-7080

For Union Chain Number US-7080

7.000 Pitch				4.500 Roller Diameter 2.750 Plate Thickness						
Type A				Type C						
Number of Teeth	Catalog Number	Stock Bore	Approx. Wgt. (lbs.)	Catalog Number	Stock Bore	Max. Bore	Pitch Dia.	Hub Dia.	L.T.B.	Approx. Wgt. (lbs.)
11	US-7080A11	1.50	379.0	US-7080C11	1.50	9.00	24.846	13.00	9.00	610.0
12	US-7080A12	1.50	449.0	US-7080C12	1.50	9.00	27.046	13.00	9.00	680.0
13	US-7080A13	1.50	525.0	US-7080C13	1.50	9.00	29.250	13.00	9.00	756.0
14	US-7080A14	1.50	607.0	US-7080C14	1.50	9.00	31.458	13.00	9.00	838.0
15	US-7080A15	1.50	695.0	US-7080C15	1.50	9.50	33.668	14.00	9.50	986.0
17	US-7080A17	1.50	890.0	US-7080C17	1.50	9.50	38.095	14.00	9.50	1,180.0
19 ¹	US-7080A19	1.50	1,070.0	US-7080C19	1.50	9.50	42.529	14.00	9.50	1,400.0
21 ¹	US-7080A21	1.50	1,300.0	US-7080C21	1.50	10.00	46.967	16.00	10.00	1,744.0
24 ¹	US-7080A24	1.50	1,609.0	US-7080C24	1.50	10.00	53.629	16.00	10.00	2,053.0
30 ¹	US-7080A30	1.50	2,325.0	US-7080C30	1.50	10.00	66.967	16.00	10.00	2,768.0

¹Furnished standard with lightening holes.